

Better Pack[®] 755eS/755eM

Versatile, Rugged and Reliable



The Better Pack 755eS and 755eM excel in demanding, fast-paced environments, especially when sealing random-sized cartons. The 755eS is engineered for 115V and the 755eM is engineered for 220V. Twenty preset buttons provide exceptional operational flexibility with one touch, quickly handling different box sizes. Since the dispensers accommodate tape that is up to 4 inches wide (10.2 cm), they are particularly good for applications requiring extra reinforcement, such as when shipping large or heavy items.

Easy to Operate

- Smooth touch, color-coded key pad with 20 pre-set tape lengths
- Random key allows for continuous, uninterrupted tape dispensing
- Side opening cover provides easy tape loading access

Safe, Convenient and Dependable

- Meets or exceeds UL, CE and CSA standards for operator and electrical safety; RoHS compliant*
- Low profile design provides pack station placement flexibility
- Heavy gauge steel frame construction and few moving parts means minimal maintenance
- Low voltage adjustable water heater warms the water, optimizing tape bonding
- Exposed, large 64 oz. (1.9 liters) water bottle provides water level visibility and easy refill

Better Pack 755eS and the Better Pack 755eM

Model #	Electrical Requirements	Preset Tape Length Range	Tape Width	Gum In or Gum Out (Tape)
755eS	115v	6" to 75" Plus up to 120" random lengths	1" to 4"	Gum In/Gum Out
755eM	220v	15.24 cm to 190.5 cm Plus up to 305 cm random lengths	2.5 cm to 10.2 cm	Gum In/Gum Out

* Certificate Copies Available Upon Request.

Better Packages Electric Water-Activated Tape Dispenser

Better Pack[®] 755eS and 755eM



	Model	Specifications
Dimensions	BP755eS BP755eM	21" L x 10.5" W x 9.5" H 53.3 cm x 26.7 cm x 24.1 cm
Shipping Weight	BP755eS BP755eM	42 lbs. 19.05 kg; Up to 600' roll of tape; Up to
Maximum Roll Size	BP755eS BP755eM	7.5" diameter Up to 182.9 m roll of tape; Up to 19.05 cm diameter
Tape Width	BP755eS BP755eM	1" to 4" 2.54 cm to 10.16 cm
Dispensing Speed	BP755eS BP755eM	32" per second 81 cm per second
Water Bottle Capacity	BP755eS BP755eM	64 ounces 1.9 liters
Electrical Requirements	BP755eS BP755eM	115V, 60 Hz, 4 Amps 220V, 50 Hz, 2 Amps
Safety Compliance	BP755eS & BP755eM	Meets or exceeds UL, CE and CSA standards, RoHS compliant*
Warranty	BP755eS & BP755eM	2 years parts and materials, 6 months labor

* Certificate Copies Available Upon Request.

The Patco Group
718-497-1527
info2@patcogroup.com
patcogroup.com